

**AMENDMENTS TO THE CLAIMS**

Please **AMEND** claims 1, 7 and 8, as shown below.

Please **ADD** claims 9-16, as shown below.

The following is a complete list of all claims in this application.

1. (Currently Amended) A liquid crystal display, comprising:  
a first substrate;  
~~a pixel electrodes~~ electrode formed on the first substrate and having a first aperture pattern;  
a second substrate provided opposing the first substrate;  
a common electrode formed on the second substrate and having a second aperture pattern;  
liquid crystal ~~material injected~~ disposed between the first substrate and the second substrate; and  
spacers provided between the first substrate and the second substrate for maintaining a predetermined gap between the first substrate and the second substrate,  
wherein center portions of the first aperture pattern and the second aperture pattern are substantially straight and formed ~~alternatingly~~ alternately in parallel, and ~~wherein~~ the spacers are positioned at ends of the second aperture pattern.

2. (Currently Amended) The liquid crystal display of claim 1, wherein the first aperture pattern includes a first aperture formed in a first direction in an upper region of the pixel ~~electrodes~~ electrode, and a second aperture formed in a lower region of the pixel ~~electrodes~~ electrode in a second direction, which forms a right angle with the first direction, and

wherein the second aperture pattern includes a first base aperture formed in the first direction at a position corresponding to the upper region of the pixel ~~electrodes~~ electrode, and a second base aperture formed in the second direction at a position corresponding to the lower region of the pixel ~~electrodes~~ electrode.

3. (Currently Amended) The liquid crystal display of claim 2, wherein the first direction forms an oblique angle with edges of the pixel ~~electrodes~~ electrode.

4. (Currently Amended) The liquid crystal display of claim 3, wherein the second aperture pattern includes a first branch aperture that overlaps upper and lower edges of the pixel ~~electrodes~~ electrode, and a second branch aperture that overlaps left and right edges of the pixel ~~electrodes~~ electrode,

wherein the first aperture pattern includes third apertures positioned at upper and lower center portions of the pixel ~~electrodes~~ electrode, and which are uniformly provided with respect to the upper and lower edges of the pixel ~~electrodes~~ electrode, and

wherein the first and second aperture patterns divide the pixel ~~electrodes~~ electrode into a plurality of closed polygonal shapes.

5. (Original) The liquid crystal display of claim 4, wherein the second branch aperture is wider than the base apertures.

6. (Currently Amended) The liquid crystal display of claim 2, wherein the first direction is formed uniformly with one edge of the pixel ~~electrodes~~ electrode.

7. (Currently Amended) A liquid crystal display, comprising:  
a first substrate;  
a pixel ~~electrodes~~ electrode formed on the first substrate having a first aperture pattern;  
a second substrate provided opposing the first substrate;  
a common electrode formed on the second substrate; and having a second aperture pattern;  
liquid crystal ~~material injected~~ disposed between the first substrate and the second substrate; and

spacers provided between the first substrate and the second substrate for maintaining a predetermined gap between the first substrate and the second substrate,

wherein the first aperture pattern includes a first aperture formed horizontally from a first side of the pixel ~~electrodes~~ electrode, and second and third apertures formed obliquely from the first aperture and symmetrically about the first aperture, and formed such that an interval between the second aperture and the third aperture decreases as approaching a second side of the pixel ~~electrodes~~ electrode, which is opposite the first side,

wherein the second aperture pattern includes (a) a base portion formed horizontally, (b) a fourth aperture having first and second branches formed obliquely from the base portion such

that a distance between the first and second branches increases in a direction away from the base portion, and having first and second branch ends formed vertically in opposite directions from distal ends respectively of the first and second branches, (c) a fifth aperture having a first center portion formed substantially in parallel with the first branch, and having first and second bends forming horizontal and vertical portions, and (d) a sixth aperture formed symmetrically with the fifth aperture about the fourth aperture,

wherein the first and second aperture patterns are formed ~~alternatingly~~ alternately when the liquid crystal display is viewed from above, and ~~wherein~~ the spacers are provided at ends of the second aperture pattern.

8. (Currently Amended) A liquid crystal display, comprising:  
a first substrate;  
a pixel electrodes electrode formed on the first substrate having a first aperture pattern;  
a second substrate provided opposing the first substrate;  
a common electrode formed on the second substrate having a second aperture pattern;  
and

liquid crystal ~~material injected~~ disposed between the first substrate and the second substrate;

wherein the first aperture pattern includes first apertures dividing an upper portion of the pixel ~~electrodes~~ electrode into vertical regions, and second apertures formed below the first apertures to divide a lower portion of the pixel ~~electrodes~~ electrode into horizontal regions,

wherein the second aperture pattern includes third apertures formed vertically, and fourth apertures formed horizontally below the third apertures, and

wherein the first apertures and the third apertures are ~~alternatingly~~ alternately formed to divide the upper portion of the pixel ~~electrodes~~ electrode into a plurality of regions, and the second apertures and fourth apertures are ~~alternatingly~~ alternately formed to divide the lower portion of the pixel ~~electrodes~~ electrode into a plurality of regions.

9. (New) A liquid crystal display, comprising:  
a first substrate;  
a pixel electrode formed on the first substrate and having an aperture pattern;  
a second substrate provided opposing the first substrate;  
a common electrode formed on the second substrate and having a first protrusion pattern and a second protrusion pattern; and  
liquid crystal disposed between the first substrate and the second substrate,  
wherein center portions of the aperture pattern and the first protrusion pattern are substantially straight and formed alternately in parallel, and the second protrusion pattern is positioned at ends of the first protrusion pattern.

10. (New) The liquid crystal display of claim 9, wherein the second protrusion pattern is sandwiched between the first substrate and the second substrate to maintain a predetermined gap between the first substrate and the second substrate.

11. (New) The liquid crystal display of claim 9, wherein the ends of the first protrusion pattern are bent out from center portions of the first protrusion pattern and overlap with a boundary line of the pixel electrode.

12. (New) A liquid crystal display, comprising:  
a first substrate;  
a pixel electrode formed on the first substrate and having an aperture pattern;  
a second substrate provided opposing the first substrate;  
a common electrode formed on the second substrate and having a first protrusion pattern  
and a second protrusion pattern; and  
liquid crystal disposed between the first substrate and the second substrate,  
wherein center portions of the aperture pattern and the first protrusion pattern are  
substantially straight and formed alternately in parallel, and the second protrusion pattern is  
positioned between two ends of the first protrusion pattern.

13. (New) The liquid crystal display of claim 12, wherein the second protrusion  
pattern is sandwiched between the first substrate and the second substrate to maintain a  
predetermined gap between the first substrate and the second substrate.

14. (New) The liquid crystal display of claim 12, wherein the ends of the first  
protrusion pattern are bent out from center portions of the first protrusion pattern and overlap a  
boundary line of the pixel electrode.

15. (New) A liquid crystal display, comprising:  
a first substrate;  
a pixel electrode formed on the first substrate and having a aperture pattern;

a second substrate provided opposing the first substrate;  
a common electrode formed on the second substrate and having a first protrusion pattern  
and a second protrusion pattern ;  
liquid crystal disposed between the first substrate and the second substrate; and  
wherein center portions of the aperture pattern and the first protrusion pattern are  
substantially straight and formed alternately in parallel, each of the aperture pattern and the first  
protrusion pattern includes a plurality of straight line patterns, and the second protrusion pattern  
is positioned between two of the plurality of straight line patterns.

16. (New) The liquid crystal display of claim 15, wherein the second protrusion  
pattern is sandwiched between the first substrate and the second substrate to maintain a  
predetermined gap between the first substrate and the second substrate.